

Specifications for the BK Series ALL_DIESEL KRACKER™

	BK-250D	BK-400D
CAPACITIES		
Sealant tank, max gals	250	400
Hydraulic fluid, gals	24	35
Diesel fuel, gals	24	35
DIMENSIONS		
	See outline drawings	
SEALANT HEATING SYSTEM		
Heating time, ambient to 375°F, in minutes (<i>Note 1</i>)	45 to 60	
Heat input, BTU/hr	375,000	425,000
Melting Rate	Highest melting rate in the industry (<i>Note 1</i>)	
GENERAL		
Tank openings, inches	21 W x 36 L	
Engine	3-cylinder diesel	
Tires	9.50 x 16.5 (E)	
Suspension	Rubber torsion axle(s)	
Brakes: standard	Electric	
optional	Hydraulic surge type	
Lights	Comply with applicable Federal Motor Carriers regulations	
Dry weight, lbs	3600	5700
Gross weight, lbs (<i>Note 2</i>)	5800	8700

NOTES:

- (1) Under normal working temperatures and conditions.
- (2) All operating fuel, fluids, and sealant tank full.
- (3) Standard BK Series equipment includes electric start; fire extinguisher; hydraulic pumping and control; stop, tail, turn indicator lamps; beacon; "BearCat Gold" paint.